

WATERPROOFS TILED AREAS WITHOUT REMOVING TILES

PACKAGING




MIXING



APPLICATION



USES



SUBSTRATES

TILED FLOORS
AND WALLS

DESCRIPTION

SHOWER FIX is a siloxane/solvent based material that penetrates deep into the grout and porous tiles, forming a water-repellent barrier. SHOWER FIX is not a coating, coatings fail if chipped or scratched and wear due to ordinary cleaning. Coatings need to be reapplied constantly and once damaged are next to useless.

USES

Shower Fix prevents moisture getting behind tiles which can cause cracking, rusting and mould.

FEATURES

- Clear and colourless
- Simple and fast to apply
- Allows grout and tiles to breathe
- Is not a coating, does not fail due to chips or scratches
- Do not have to remove tiles

COVERAGE (Approximate) 500mL will treat approximately 15m².

PERFORMANCE DATA

Test conducted with a moisture metre show that no moisture passes through areas that has been sealed.

SPECIFICATIONS

The water proofing compound shall penetrate into porous or cracked areas and stop moisture penetration, such as shower fix manufactured by Construction Chemicals and shall be applied in accordance with the manufacturer's application instructions.

SURFACE PREPARATION

Ensure all surfaces are visually dry and mould free (SHOWER FIX actually works more effectively with some moisture). Remove all silicone or acrylic sealant from tile joints and corners. Clean tiles and existing grout thoroughly to remove any mould or mildew. Rake out any crumbling or loose grout and replace with Construction Chemicals coloured KEMGROUT. Allow at least 24 hours for new grout to cure sufficiently prior to treatment with SHOWER FIX.

APPLICATION

Apply SHOWER FIX liberally to tiled areas using a small brush, paying particular attention to grout lines. Almost immediately after the first application, apply a second coat "wet on wet". Allow approximately 5 minutes before wiping off excess with a soft cloth. Always allow 24 hours before using the shower. Shower Fix is a clear, undetectable treatment,

however it is recommended to apply to a small inconspicuous area to ensure satisfactory performance. After recommended drying time, apply Construction Chemicals COLOUR SEAL, a flexible coloured acrylic sealant, to all corner joints.

CLEAN UP Use mineral turps.

SAFETY

Contains flammable solvents, do not smoke or expose to naked flames and/or electrical equipment. Ensure adequate ventilation during application and drying period. Avoid contact with skin or eyes. It is recommended to wear gloves and if necessary eye protection during application. If swallowed do not induce vomiting, give glass of water and contact a doctor or poisons information centre.

SHELF LIFE 2 years

**CONSTRUCTION
CHEMICALS**

1ADELAIDE 467 - 469 SOUTH RD REGENCY PARK 5010 PH: (08) 8346 8013 FAX: (08) 8340 2052
1BRISBANE 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892
1MELBOURNE 11 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748
1PERTH 11 COLLIE RD WELSHPOOL 6106 PH: (08) 9356 9999 FAX: (08) 9356 9955
1SYDNEY 31 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534
1AUCKLAND 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236
1KUALA LUMPUR LOT 2 JALAN KECAPI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING 40000 SHAH ALAM PH: (603) 5122 2522 FAX: (603) 5122 2526

"The information contained in this technical publication is based on our current knowledge and experience and is provided as a guide only. In view of the many factors that may affect application it is the users sole responsibility to ensure suitability for a specific purpose."